

1. Identification

Product identifier SUPER STRIP

Other means of identification

SDS number 576N66A

Product code HIL00152

Recommended use Stripper

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.
 St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300
 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1
 Serious eye damage/eye irritation Category 1
 Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory irritation.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| Ethylene glycol monobutyl ether | | 111-76-2 | 20 - < 30 |
| Ethanol, 2-amino- | | 141-43-5 | 5 - < 10 |
| POTASSIUM HYDROXIDE | | 1310-58-3 | 1 - < 3 |
| Silicic acid, Sodium Salt | | 6834-92-0 | 1 - < 3 |
| Other components below reportable levels | | | 60 - < 70 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|--|--|

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components | Type | Value |
|--|------|------------------------------|
| Ethanol, 2-amino- (CAS 141-43-5) | PEL | 6 mg/m3 |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | PEL | 3 ppm 240 mg/m3 50 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|--|---------|---------|
| Ethanol, 2-amino- (CAS 141-43-5) | STEL | 6 ppm |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | TWA | 3 ppm |
| POTASSIUM HYDROXIDE (CAS 1310-58-3) | TWA | 20 ppm |
| | Ceiling | 2 mg/m3 |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|--|------|---------------------------|
| Ethanol, 2-amino- (CAS 141-43-5) | STEL | 15 mg/m3 |
| | TWA | 6 ppm 8 mg/m3 3 ppm |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | TWA | 24 mg/m3 |
| POTASSIUM HYDROXIDE (CAS 1310-58-3) | TWA | 5 ppm 2 mg/m3 |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|--|----------|--|---------------------|---------------|
| Ethylene glycol monobutyl ether (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene glycol monobutyl ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use safety eyewear with splash guards or side shields, chemical goggles, or face shields.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Avoid contact with the skin. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Wear impervious/slip resistant boots such as Hillyard Stripping Boots while standing in the stripping solution.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge.

Thermal hazards

None known.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Clear, colorless to light amber liquid

Physical state

Liquid.

Form

Liquid.

Color

Colorless to Light Amber

Odor

Mild solvent odor

Odor threshold

Not available

pH

Not available.

Melting point/freezing point

Not applicable / Not available

Initial boiling point and boiling range

213 °F (100.56 °C) Corr.

Flash point

> 213.0 °F (> 100.6 °C) Tag Closed Cup

Evaporation rate

< 1 Slower than 1 Ethyl ether = 1

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

16.3 mm Hg

Vapor density

1.5 Air=1

Relative density

1.052 at 77°F

Solubility(ies)

Solubility (water)

100 % Complete

| | |
|--|------------------|
| Partition coefficient (n-octanol/water) | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | Not available |
| Other information | |
| Density | 8.76 lb/gal |
| Percent volatile | 81 - 86 % |
| VOC (Weight %) | 33 % Concentrate |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | Reacts violently with strong acids. This product may react with oxidizing agents. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Do not mix with other chemicals. Contact with incompatible materials. |
| Incompatible materials | Acids. Strong oxidizing agents. Oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | May cause irritation to the respiratory system. Prolonged inhalation may be harmful. |
| Skin contact | Causes severe skin burns. Harmful in contact with skin. |

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and central nervous system effects. Harmful in contact with skin. May cause respiratory irritation.

| Product | Species | Test Results |
|-------------------|------------|--|
| SUPER STRIP | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 63297.8711 ml/kg estimated 1407.4338 mg/kg estimated |
| <i>Inhalation</i> | | |
| LC50 | Guinea pig | 6135135 ppm, 6 Hours |
| | Mouse | 319672.125 mg/l, 4 Hours 2745.0981 ppm, 7 Hours estimated |
| | Rat | 1764.7059 ppm, 4 Hours estimated |
| <i>Oral</i> | | |
| LD50 | Guinea pig | 4.7048 g/kg estimated |
| | Mouse | 4.6914 g/kg estimated |

| Product | Species | Test Results |
|--|------------|---------------------------|
| | Rabbit | 1.2549 g/kg estimated |
| | Rat | 1929.3727 mg/kg estimated |
| Components | Species | Test Results |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 400 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 700 ppm, 7 Hours |
| | Rat | 450 ppm, 4 Hours |
| <i>Oral</i> | | |
| LD50 | Guinea pig | 1.2 g/kg |
| | Mouse | 1.2 g/kg |
| | Rabbit | 0.32 g/kg |
| | Rat | 560 mg/kg |
| POTASSIUM HYDROXIDE (CAS 1310-58-3) | | |
| Acute | | |
| <i>Oral</i> | | |
| LD50 | Rat | 273 mg/kg |

* Estimates for product may be based on additional component data not shown.

| | |
|---|--|
| Skin corrosion/irritation | Causes severe skin burns and eye damage. |
| Serious eye damage/eye irritation | Causes serious eye damage. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | 3 Not classifiable as to carcinogenicity to humans. |
| US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | |
| Not listed. | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | May be harmful if absorbed through skin. Prolonged inhalation may be harmful. |
| | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |
| | Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans. |

12. Ecological information

| | |
|--------------------|--|
| Ecotoxicity | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. |
|--------------------|--|

| Product | Species | | Test Results |
|--|---------|--|------------------------------------|
| SUPER STRIP | | | |
| Aquatic | | | |
| Fish | LC50 | Fish | 1700.6345 mg/l, 96 hours estimated |
| Components | Species | | Test Results |
| Ethanol, 2-amino- (CAS 141-43-5) | | | |
| Aquatic | | | |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 114 - 196 mg/l, 96 hours |
| Ethylene glycol monobutyl ether (CAS 111-76-2) | | | |
| Aquatic | | | |
| Fish | LC50 | Inland silverside (Menidia beryllina) | 1250 mg/l, 96 hours |
| POTASSIUM HYDROXIDE (CAS 1310-58-3) | | | |
| Aquatic | | | |
| Fish | LC50 | Western mosquitofish (Gambusia affinis) | 80 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|---------------------------------|-------|
| Ethanol, 2-amino- | -1.31 |
| Ethylene glycol monobutyl ether | 0.83 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | NA1760 |
| UN proper shipping name | Compound, Cleaning Liquid, (Potassium Hydroxide, Monoethanolamine) |
| Transport hazard class(es) | |
| Class | 8 |
| Subsidiary risk | - |
| Label(s) | 8 |
| Packing group | II |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |

**General information**

This material is regulated under IATA and IMDG regulations. Contact manufacturer for shipping instructions.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

POTASSIUM HYDROXIDE (CAS 1310-58-3) Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. Massachusetts RTK - Substance List

Ethanol, 2-amino- (CAS 141-43-5)
Ethylene glycol monobutyl ether (CAS 111-76-2)
POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol, 2-amino- (CAS 141-43-5)
Ethylene glycol monobutyl ether (CAS 111-76-2)
POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol, 2-amino- (CAS 141-43-5)
Ethylene glycol monobutyl ether (CAS 111-76-2)
POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. Rhode Island RTK

POTASSIUM HYDROXIDE (CAS 1310-58-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|---------------|--|
| Issue date | 11-17-2014 |
| Revision date | 02-23-2016 |
| Version # | 03 |
| HMIS® ratings | Health: 3 Flammability: 0 Physical hazard: 0 |

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.

Revision Information Product and Company Identification: Product and Company Identification
Physical & Chemical Properties: Multiple Properties
Physical and chemical properties: Appearance
Physical and chemical properties: Color
Toxicological Information: Toxicological Data