

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 20-Jun-2025

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name: STRATEGIC CLEANER

Product Code: 5822

Recommended Use: Cleaning agent

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone

Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irritation: Category 2A Flammable liquids Category 3

Label elements

Signal word:

Symbols:

Warning



Hazard statements: Causes serious eye irritation Physical hazards: Flammable liquid and vapor

Precautionary Statements -

Prevention:

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/clothing and eye/face protection

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

Keep container tightly closed

Ground and bond container and receiving equipment

Use explosion-proof electrical, ventilating and lighting equipment

Use non-sparking tools

Take action to prevent static discharges

Precautionary Statements -

Response:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Fire: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Precautionary Statements - Storage: Store in a well-ventilated place. Keep cool.

Precautionary Statements -

Disposal:

Dispose of contents and container in accordance with local, state and federal regulations.

Dispose of contents and container in accordance with local, state and rederal regulations

Hazards not otherwise classified

(HNOC):

Not applicable

Other hazards: • Harmful if swallowed

Causes mild eye irritation.

• Inhalation of vapors or mist may cause respiratory irritation.

Keep out of reach of children

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Water	7732-18-5	60-80
Isopropyl Alcohol	67-63-0	10-30
Methoxyisopropanol	107-98-2	5-10
C9-11 Alcohols Ethoxylated	68439-46-3	0.1-1
Fragrance	PROPRIETARY	<0.1
Colorant	PROPRIETARY	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Eye contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Skin contact: Wash with soap and water. If skin irritation occurs: Get medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison center or physician if you feel unwell.

Ingestion: Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention if you feel unwell.

Note to physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical. Water spray (fog). Alcohol resistant foam. Carbon dioxide. Move containers

from fire area if you can do it without risk.

Specific Hazards Arising from the

Chemical:

Vapors may travel to areas away from work site before igniting/flashing back to vapor

source.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters:

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Remove all sources of ignition. Avoid contact with skin, eyes or clothing. Use personal

protective equipment as required.

Environmental Precautions:

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Methods for cleaning up: Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on safe handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions: Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Isopropyl Alcohol	TWA: 200 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	STEL: 400 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	_
Methoxyisopropanol	TWA: 50 ppm	(vacated) TWA: 100 ppm	TWA: 100 ppm
107-98-2	STEL: 100 ppm	(vacated) TWA: 360 mg/m ³	TWA: 360 mg/m ³
		(vacated) STEL: 150 ppm	STEL: 150 ppm
		(vacated) STEL: 540 mg/m ³	STEL: 540 mg/m ³

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear splash goggles.

Skin and body protection: Wear rubber or other chemical-resistant gloves.

Respiratory protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

ASTM D56

3 should be considered.

General hygiene considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid
Color: Light green
Odor: solvent

Odor Threshold: No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH: 9.0-10.0

Melting Point / Freezing Point: No data available

Boiling Point / Boiling Range: 84 °C / 183 °F **Flash Point:** 36 °C / 97 °F

Evaporation Rate: < 1 (Butyl acetate = 1)
Flammability (solid, gas): No data available No information available
Flammability Limits in Air: No information available

Upper Flammability Limit: No data available

Lower Flammability Limit:No data availableVapor Pressure:No data availableNo information availableVapor Density:No data availableNo information available

Relative Density: 0.974

Solubility(ies): Soluble in water

Partition Coefficient: No data available No information available

Autoignition Temperature: Not applicable **Decomposition Temperature:** Not applicable

Kinematic Viscosity: No information available No information available

Particle characteristics: Not applicable

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight **Incompatible materials:** Strong oxidizing agents. Strong acids.

Hazardous decomposition products: May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

Eye contact: Pain, redness and swelling of the conjunctiva.

Skin contact: Pain, redness and cracking of the skin.

Inhalation: Nasal discomfort and coughing.

Ingestion: Nasai discomfort and cougning.

Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

Product Information:

Data not available or insufficient for classification.

Target organ effects:

Central nervous system. Eyes. Respiratory system. Skin.

Acute toxicity

Numerical measures of toxicity:

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 19,994.70 mg/kg
ATEmix (dermal) 21,206.70 mg/kg
ATEmix (inhalation-vapor) 130.10 mg/l

Component Information:

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Water	> 90 mL/kg (Rat)	-	-	
7732-18-5	-			
Isopropyl Alcohol 67-63-0	4710 - 5840 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h	
Methoxyisopropanol 107-98-2	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat)6 h	
C9-11 Alcohols Ethoxylated 68439-46-3	= 1400 mg/kg (Rat)	-	-	

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Isopropyl Alcohol 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
Methoxyisopropanol				

107-98-2 - LC50: =20.8g/L (96h, - EC50: =23300mg/L (48h, Pimephales promelas) - Daphnia magna)

Persistence and Degradability:Bioaccumulation:
No information available.
No information available.

Mobility in Soil:No information availableOther adverse effects:No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues/unused

products:

Dispose of in accordance with federal, state and local regulations.

Contaminated packaging: Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

UN/ID No: UN1993

Proper Shipping Name: Flammable liquids, n.o.s., (contains isopropanol)

Hazard Class: 3
Packing Group: III

Special Provisions: Class 3, Packing Group III materials meet the exception requirements of section 49 CFR

173.150 when individual containers of not more than 1.3 gallons are packed in a strong outer packaging and ground transportation is utilized. Such containers may be reclassified

as "Limited Quantity".

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN number or ID number: UN1993

Proper Shipping Name: Flammable liquids, n.o.s., (contains isopropanol)

Hazard Class: 3
Packing Group: III

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute health hazard:

Chronic Health Hazard:

Fire hazard:

Sudden release of pressure hazard:

No

Reactive Hazard:

No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health hazards: 2 Flammability: 3 Instability: 0 Special hazards: -

HMIS Health hazards: 2 Flammability: 3 Physical hazards: 0

Revision Date: 20-Jun-2025

Revision Note: Section, 3, 7, 9, 11, 12

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Page 6/6