



# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/27/2017

Supersedes:04/05/2016

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : TR-3 RESIN GLAZE 16 FL.OZ.  
Product code : 12A-6

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Automobile Cleaner & Polish

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 4 H227  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H227 - Combustible liquid  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P264 - Wash affected areas thoroughly after handling  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P321 - Specific treatment: See section 4.1 on SDS  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Name                                        | Product identifier  | %       | GHS-US classification                                                                                                                    |
|---------------------------------------------|---------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------|
| Distillates (Petroleum), Hydrotreated Light | (CAS No) 64742-47-8 | 15 - 20 | Asp. Tox. 1, H304                                                                                                                        |
| Diatomaceous Earth, Uncalcined              | (CAS No) 61790-53-2 | 10 - 20 | Not classified                                                                                                                           |
| Kerosene                                    | (CAS No) 8008-20-6  | 10 - 14 | Asp. Tox. 1, H304                                                                                                                        |
| Fatty Acids, Tall-Oil                       | (CAS No) 61790-12-3 | 3 - 5   | Not classified                                                                                                                           |
| Morpholine                                  | (CAS No) 110-91-8   | 1 - 2   | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 3 (Dermal), H311<br>Acute Tox. 4 (Inhalation), H332<br>Skin Corr. 1A, H314 |

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice.
- Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/injuries after skin contact : Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking.

Hygiene measures : Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |                                     |                                                                                                                                                                                                                                  |
|----------------------------------------------------------|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USA ACGIH                                                | ACGIH TWA (ppm)                     | 200 ppm 8 Hours                                                                                                                                                                                                                  |
| Kerosene (8008-20-6)                                     |                                     |                                                                                                                                                                                                                                  |
| USA ACGIH                                                | ACGIH TWA (mg/m <sup>3</sup> )      | 200 mg/m <sup>3</sup> (Kerosene/Jet fuels, as total hydrocarbon vapor; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Application restricted to conditions in which there are negligible aerosol exposures) |
| Morpholine (110-91-8)                                    |                                     |                                                                                                                                                                                                                                  |
| USA ACGIH                                                | ACGIH TWA (mg/m <sup>3</sup> )      | 70 mg/m <sup>3</sup>                                                                                                                                                                                                             |
| USA ACGIH                                                | ACGIH TWA (ppm)                     | 20 ppm (Morpholine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)                                                                                                                                          |
| USA OSHA                                                 | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 70 mg/m <sup>3</sup>                                                                                                                                                                                                             |
| USA OSHA                                                 | OSHA PEL (TWA) (ppm)                | 20 ppm                                                                                                                                                                                                                           |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|                                             |                            |
|---------------------------------------------|----------------------------|
| Physical state                              | : Liquid                   |
| Appearance                                  | : Liquid.                  |
| Color                                       | : Tan.                     |
| Odor                                        | : Paraffin odour.          |
| Odor threshold                              | : No data available        |
| pH                                          | : 8.5                      |
| Relative evaporation rate (butyl acetate=1) | : No data available        |
| Melting point                               | : No data available        |
| Freezing point                              | : No data available        |
| Boiling point                               | : No data available        |
| Flash point                                 | : 82 °C                    |
| Auto-ignition temperature                   | : No data available        |
| Decomposition temperature                   | : No data available        |
| Flammability (solid, gas)                   | : No data available        |
| Vapor pressure                              | : No data available        |
| Relative vapor density at 20 °C             | : No data available        |
| Relative density                            | : 0.98                     |
| Solubility                                  | : Poorly soluble in water. |
| Log Pow                                     | : No data available        |
| Log Kow                                     | : No data available        |
| Viscosity, kinematic                        | : 2000 - 3000 cSt          |
| Viscosity, dynamic                          | : No data available        |
| Explosive properties                        | : No data available        |
| Oxidizing properties                        | : No data available        |
| Explosion limits                            | : No data available        |

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

##### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                            |                                                                |
|----------------------------|----------------------------------------------------------------|
| LD50 oral rat              | > 5000 mg/kg body weight                                       |
| LD50 dermal rabbit         | > 2000 mg/kg                                                   |
| LC50 inhalation rat (mg/l) | > 5.28 mg/l/4h Based on lack of mortality and systemic effects |

##### Kerosene (8008-20-6)

|               |                     |
|---------------|---------------------|
| LD50 oral rat | > 15000 mg/kg (Rat) |
|---------------|---------------------|

##### Fatty Acids, Tall-Oil (61790-12-3)

|               |                    |
|---------------|--------------------|
| LD50 oral rat | > 3200 mg/kg (Rat) |
|---------------|--------------------|

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Morpholine (110-91-8)</b> |                        |
|------------------------------|------------------------|
| LD50 oral rat                | 1900 mg/kg body weight |
| LD50 dermal rabbit           | 500 mg/kg body weight  |
| LC50 inhalation rat (mg/l)   | 24 mg/l/4h             |

|                                   |                                             |
|-----------------------------------|---------------------------------------------|
| Skin corrosion/irritation         | : Causes skin irritation.<br>pH: 8.5        |
| Serious eye damage/irritation     | : Causes serious eye irritation.<br>pH: 8.5 |
| Respiratory or skin sensitization | : Not classified                            |
| Germ cell mutagenicity            | : Not classified                            |
| Carcinogenicity                   | : Not classified                            |

| <b>Kerosene (8008-20-6)</b> |   |
|-----------------------------|---|
| IARC group                  | 3 |

| <b>Morpholine (110-91-8)</b> |   |
|------------------------------|---|
| IARC group                   | 3 |

| <b>Diatomaceous Earth, Uncalcined (61790-53-2)</b> |   |
|----------------------------------------------------|---|
| IARC group                                         | 3 |

|                                                     |                                                                                                                                  |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Reproductive toxicity                               | : Not classified                                                                                                                 |
| Specific target organ toxicity – single exposure    | : Not classified                                                                                                                 |
| Specific target organ toxicity – repeated exposure  | : Not classified                                                                                                                 |
| Aspiration hazard                                   | : Not classified                                                                                                                 |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met.                                                              |
| Symptoms/injuries after inhalation                  | : May cause allergy or asthma symptoms or breathing difficulties if inhaled.                                                     |
| Symptoms/injuries after skin contact                | : Itching. Red skin. Skin rash/inflammation. Causes skin irritation.                                                             |
| Symptoms/injuries after eye contact                 | : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation. |
| Symptoms/injuries after ingestion                   | : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.                                  |

## SECTION 12: Ecological information

### 12.1. Toxicity

| <b>Fatty Acids, Tall-Oil (61790-12-3)</b> |                                   |
|-------------------------------------------|-----------------------------------|
| LC50 fish 1                               | >= 1000 mg/l (LC50; 96 h; Pisces) |
| EC50 Daphnia 1                            | >= 1000 mg/l (EC50; 48 h)         |

| <b>Morpholine (110-91-8)</b> |                       |
|------------------------------|-----------------------|
| LC50 fish 1                  | 180 mg/l (LC50; 96 h) |
| EC50 Daphnia 1               | 119 mg/l (EC50; 24 h) |

### 12.2. Persistence and degradability

| <b>TR-3 RESIN GLAZE 16 FL.OZ.</b> |                  |
|-----------------------------------|------------------|
| Persistence and degradability     | Not established. |

| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                  |
|-----------------------------------------------------------------|------------------|
| Persistence and degradability                                   | Not established. |

| <b>Kerosene (8008-20-6)</b>   |                                                               |
|-------------------------------|---------------------------------------------------------------|
| Persistence and degradability | Biodegradability in soil: no data available. Not established. |

| <b>Fatty Acids, Tall-Oil (61790-12-3)</b> |                                 |
|-------------------------------------------|---------------------------------|
| Persistence and degradability             | Readily biodegradable in water. |

| <b>Morpholine (110-91-8)</b>    |                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air. |
| Biochemical oxygen demand (BOD) | 0.02 g O <sub>2</sub> /g substance                                                      |
| ThOD                            | 2.6 g O <sub>2</sub> /g substance                                                       |
| BOD (% of ThOD)                 | 0.009                                                                                   |

| <b>Diatomaceous Earth, Uncalcined (61790-53-2)</b> |                                   |
|----------------------------------------------------|-----------------------------------|
| Persistence and degradability                      | Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD)                    | Not applicable                    |
| Chemical oxygen demand (COD)                       | Not applicable                    |

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                                                 |                                                                               |
|-----------------------------------------------------------------|-------------------------------------------------------------------------------|
| <b>Diatomaceous Earth, Uncalcined (61790-53-2)</b>              |                                                                               |
| ThOD                                                            | Not applicable                                                                |
| <b>12.3. Bioaccumulative potential</b>                          |                                                                               |
| <b>TR-3 RESIN GLAZE 16 FL.OZ.</b>                               |                                                                               |
| Bioaccumulative potential                                       | Not established.                                                              |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                                                                               |
| Bioaccumulative potential                                       | Not established.                                                              |
| <b>Kerosene (8008-20-6)</b>                                     |                                                                               |
| Bioaccumulative potential                                       | No bioaccumulation data available. Not established.                           |
| <b>Fatty Acids, Tall-Oil (61790-12-3)</b>                       |                                                                               |
| Log Pow                                                         | 4.89 - 5.98                                                                   |
| Bioaccumulative potential                                       | Not established.                                                              |
| <b>Morpholine (110-91-8)</b>                                    |                                                                               |
| BCF fish 1                                                      | < 2.3 (BCF)                                                                   |
| BCF fish 2                                                      | < 2.8 (BCF)                                                                   |
| Log Pow                                                         | -2.55 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method) |
| Bioaccumulative potential                                       | Low potential for bioaccumulation (BCF < 500).                                |
| <b>Diatomaceous Earth, Uncalcined (61790-53-2)</b>              |                                                                               |
| Bioaccumulative potential                                       | No bioaccumulation data available.                                            |
| <b>12.4. Mobility in soil</b>                                   |                                                                               |
| <b>Morpholine (110-91-8)</b>                                    |                                                                               |
| Surface tension                                                 | 0.0375 N/m                                                                    |

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not Regulated,  
ICAO/IATA (air): Not Regulated,  
IMO/IMDG (water): Not Regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not Regulated

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### TR-3 RESIN GLAZE 16 FL.OZ.

|                                     |                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Fire hazard<br>Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|-----------------------------------------------------------------------------------|

##### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                     |                                                                    |
|-------------------------------------|--------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|--------------------------------------------------------------------|

##### Fatty Acids, Tall-Oil (61790-12-3)

|                                                                           |                                 |
|---------------------------------------------------------------------------|---------------------------------|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                 |
| SARA Section 311/312 Hazard Classes                                       | Immediate (acute) health hazard |

##### Morpholine (110-91-8)

|                                     |                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Fire hazard<br>Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|-----------------------------------------------------------------------------------|

#### 15.2. International regulations

##### CANADA

##### TR-3 RESIN GLAZE 16 FL.OZ.

|                      |                                         |
|----------------------|-----------------------------------------|
| WHMIS Classification | Class B Division 3 - Combustible Liquid |
|----------------------|-----------------------------------------|

##### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                                       |                                                                 |
|-------------------------------------------------------|-----------------------------------------------------------------|
| Listed on the Canadian DSL (Domestic Substances List) |                                                                 |
| WHMIS Classification                                  | Uncontrolled product according to WHMIS classification criteria |

##### Fatty Acids, Tall-Oil (61790-12-3)

|                                                       |  |
|-------------------------------------------------------|--|
| Listed on the Canadian DSL (Domestic Substances List) |  |
|-------------------------------------------------------|--|

##### Morpholine (110-91-8)

|                      |                                                                                                                                                                        |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WHMIS Classification | Class B Division 2 - Flammable Liquid<br>Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects<br>Class E - Corrosive Material |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### EU-Regulations

##### Fatty Acids, Tall-Oil (61790-12-3)

|                                                                                                                                                                                          |  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) |  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.3; R40  
Xi; R36/38

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

##### Fatty Acids, Tall-Oil (61790-12-3)

|                                                                                           |  |
|-------------------------------------------------------------------------------------------|--|
| Listed on the AICS (Australian Inventory of Chemical Substances)                          |  |
| Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory                |  |
| Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) |  |

#### 15.3. US State regulations

##### TR-3 RESIN GLAZE 16 FL.OZ.

|                                                                     |                                    |
|---------------------------------------------------------------------|------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List               | No                                 |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No                                 |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No                                 |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No                                 |
| State or local regulations                                          | U.S. - California - Proposition 65 |

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |                                                             |                                                                     |                                                                   |                                   |
|----------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List    | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No                                                       | No                                                          | No                                                                  | No                                                                |                                   |
| Kerosene (8008-20-6)                                     |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List    | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No                                                       | No                                                          | No                                                                  | No                                                                |                                   |
| Fatty Acids, Tall-Oil (61790-12-3)                       |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List    | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No                                                       | No                                                          | No                                                                  | No                                                                |                                   |
| Morpholine (110-91-8)                                    |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List    | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No                                                       | No                                                          | No                                                                  | No                                                                |                                   |
| Diatomaceous Earth, Uncalcined (61790-53-2)              |                                                             |                                                                     |                                                                   |                                   |
| U.S. - California - Proposition 65 - Carcinogens List    | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No                                                       | No                                                          | No                                                                  | No                                                                |                                   |

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:

|      |                                              |
|------|----------------------------------------------|
| H226 | Flammable liquid and vapor                   |
| H227 | Combustible liquid                           |
| H302 | Harmful if swallowed                         |
| H304 | May be fatal if swallowed and enters airways |
| H311 | Toxic in contact with skin                   |
| H314 | Causes severe skin burns and eye damage      |
| H315 | Causes skin irritation                       |
| H319 | Causes serious eye irritation                |
| H332 | Harmful if inhaled                           |

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



## HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 2 Moderate Hazard

Physical

: 0 Minimal Hazard

Personal Protection

: B

SDS US (GHS HazCom 2012) - TCC

# TR-3 RESIN GLAZE 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*