

HMIS RATING	
Health	1
Flammability	4
Reactivity	0

MATERIAL SAFETY DATA SHEET

NFPA 704 RATING	
Health	1
Flammability	4
Reactivity	0
NFPA 30B LEVEL	
3	

KIMBALL-MIDWEST
 P.O. BOX 2470
 COLUMBUS, OH 43216-2470
 CORPORATE TELEPHONE: 614-219-6100
 EMERGENCY TELEPHONE: 800-424-9300

1. PRODUCT IDENTIFICATION

PART NUMBER..... 80-474
 PRODUCT NAME..... Battery Terminal Protector
 CHEMICAL FAMILY..... N/A
 DOT SHIPPING..... Limited Quantity (LQ)

2. HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	ACGIH TLV	STEL	%
N-hexane (64742-49-0)	50ppm	50ppm		55
Propane/Isobutane/N-butane (68476-86-8)	800ppm	800ppm		25
Petroleum oils (64742-52-5, 64742-01-4)	100ppm	100ppm		4

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement.

3. PHYSICAL DATA

BOILING POINT (RANGE).....-43-387°F
 VAPOR PRESSURE PSIG @ 70°F.....80-90
 VAPOR DENSITY (AIR = 1).....>1
 SOLUBILITY IN WATER.....Negligible
 SPECIFIC GRAVITY (H₂O = 1).....0.6871
 MELTING/FREEZING POINT.....N/A
 EVAPORATION RATE (Ether=1).....>1
 VOC content (by weight).....73.5%
 APPEARANCE AND ODOR.....Red color/ solvent odor

4. FIRE AND EXPLOSION DATA

FLASH POINT.....-141°F PMCC
 UPPER EXPLOSIVE LIMIT (%).....9.5
 LOWER EXPLOSIVE LIMIT (%).....0.7
 EXTINGUISHING MEDIA.....Dry chemical, CO₂, foam, water fog
 SPECIAL FIREFIGHTING PROCEDURES.....Container can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE AND EXPLOSION HAZARDS.....Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause injury or death. Empty drums should be completely drained, properly banded and promptly returned to a drum reconditioner, or properly disposed of.

5. HEALTH EFFECTS DATA

SHORT TERM EFFECTS OF EXPOSURE

ROUTE OF ENTRY.....Eyes, Skin, Inhalation
 HEALTH HAZARDS (ACUTE AND CHRONIC).....Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion. Overexposure may cause nervous system damage, lung damage, kidney damage.
 EYE CONTACT.....Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of a fine dust in the eyes.
 SKIN CONTACT.....Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.
 INHALATION.....Headaches, dizziness, nausea, decreased blood pressure, changes in hear rate and cyanosis may result from overexposure to vapor or skin exposure. Prolonged inhalation may be harmful.
 INGESTION.....This material may be harmful or fatal if swallowed. If a corrosive product, may cause severe and permanent damage to the mouth throat and stomach.

5. HEALTH EFFECTS DATA CON'T.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE.....None known

FIRST AID PROCEDURES

EYES.....Flush with water for at least 15 minutes, obtain medical attention.
 SKIN CONTACT.....Wash with soap, large volumes of water. Obtain medical attention immediately.
 INGESTION.....Do not induce vomiting, obtain immediate medical attention.
 INHALATION.....Remove to fresh air. Restore breathing and keep calm and warm.

SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines).....None.

6. REACTIVITY

STABILITY.....Stable
 INCOMPATIBILITIES.....Strong acids, alkalis, oxidizers and amines. Avoid all sources of ignition, welding arcs, and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS.....Oxides of carbon, nitrogen.
 HAZARDOUS POLYMERIZATION.....Will not occur
 HAZARDOUS POLYMERIZATION CONDITIONS.....None known

7. PRECAUTIONS FOR SAFE HANDLING & USE

PROTECTIVE EQUIPMENT REQUIREMENTS.....Safety glasses; protective neoprene gloves; ventilation sufficient to maintain vapor concentrations below TLV; wear NIOSH approved respirator if TLV is exceeded
 WASH REQUIREMENTS.....Wash with soap and water.
 SPILL OR LEAK PROCEDURES.....Remove all sources of ignition; use absorbent sweeping compound to soak up material; wash area to prevent slipping
 WASTE DISPOSAL METHODS.....Dispose of in accordance with local, state, and federal hazardous waste regulations
 HANDLING & STORAGE.....Store below 120°F; keep away from heat, sparks, or open flame; do not incinerate aerosol cans
 OTHER PRECAUTIONS.....Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.

